



Personas™ 70 Scalable

- **Scalable expansion**
- **Compact size**
- **Revenue opportunities**
- **Advertising potential**
- **Convenience**

NCR's intelligent and highly functional Self-Service TouchPoints™ can turn your existing infrastructure into a strategic weapon. Our solutions help you to build better customer relationships, generate new revenue streams and migrate more transactions to a cost-efficient channel. Our web enabled Self-Service TouchPoints are the physical presence required for e-commerce fulfilment and mobile lifestyles. Making the virtual tangible.

As the customer grows more and more used to getting the service they need from an ATM, they expect the ATM to be located for their convenience.

The **Personas 70** compact size is ideal for locations where space is a premium, whether in convenience stores, gas stations or company premises.

The **Personas 70** is an interior ATM which, in addition to dispensing cash, provides services such as account transactions and inquiries. There is also a clear opportunity for generating additional revenue by dispensing non-cash items such as stamps, tickets and coupons. The high quality graphic

printer allows for the easy inclusion of logos and other graphical images and can be used, for example, to print discount vouchers.

The **Personas 70** offers sidecar expansion - to meet your customers' needs now and in the future through offering you the ability to add services when you require them. The **Personas 70** also offers you the opportunity of 3 different security safes - UL, Business hour, CEN - depending on your requirements. In short, the **Personas 70** allows you to start from where you are and grow to where you want to be.

We understand that you need to differentiate your ATMs from the competition. Branding is essential in non-bank locations. NCR offers a complete color customization service to match and reinforce your brand identity wherever the location. An optional, integrated light panel is also available allowing you to enhance your brand. To protect your investment, the modules will be fully upgradeable in the future.

The **Personas 70** is part of a comprehensive portfolio of Self-Service Solutions from NCR, focused on quality and reliability, on delivering an enhanced range of solutions for our customers, and an improved range of services for the consumer.



The **Personas 70** from NCR. Cash and more – wherever your customers are.

Specifications

<p>Multimedia Interface</p> <p>10" (254mm) VGA color screen 7.7" (196mm) VGA color flat panel Optional advert light panel 8 tactile function display keys Ruggedized tactile 16 key keyboard Swipe, dip or motorized card reader Motorized and dip card readers with smart card option EMV 3.1.1 compliant smart card reader Digitized audio system</p>	<p>PRODUCT DIMENSIONS</p> <p>Height 53.3" (1354mm) Width 18.5" (470mm) Depth 28.8" (731.5mm) Weight max. 1071lbs (486kg) – CEN A3 security Weight min. 408lbs (185kg) – UL 291 Business hours</p> <p>DISPENSER</p> <p>1,2,3 or 4 denomination options with bunch (retract) and spray options NCR universal polycarbonate multimedia cassette with 11.6" (295mm) capacity</p> <p>SECURITY</p> <p>Physical UL 291 Business hours UL 291 Level 1 CEN Grade A3</p> <p>INFORMATION</p> <p>HI-BAPE (DES) EKC (DES, RSA limited to initial key exchange), enhanced physical protection</p> <p>ELECTRONIC PLATFORM</p> <p>Multiple Pentium® processing</p> <p>ACCESSIBILITY</p> <p>Subject to compliance with NCR site preparation and installation guidelines, the NCR P70 complies with ADAAG 4.34.2, 4.34.3, and 4.34.4. NCR cannot certify or warrant compliance with ADAAG 4.34.5.</p>	<p>ELECTROMAGNETIC COMPATIBILITY</p> <p>Emission</p> <p>FCC Category A (USA) EN 55022 (1987) Class A VDE 0871/75 Class A CISPR 22 Class A</p> <p>Immunity</p> <p>EN 50082-1 Part 1 (1992) Generic Immunity Standard Radiated Immunity – IEC 801-4-3 Electrostatic Discharge – IEC 801-4-2 Fast Transients – IEC 801-4-4</p> <p>EMC Directives</p> <p>89/336/EEC EMC Directive 92/31/EEC Amending EMC Directive 73/23/EEC Low Voltage Directive</p> <p>SAFETY HOUSE COMPATIBILITY</p> <p>UL 291 CAN/CSA – C22.2 no. 950 EN60 950</p> <p>ENVIRONMENTAL</p> <p>Operating temperature: 50°F (10°C) to 104°F (40°C) Relative humidity: 20% to 80%</p> <p>ACOUSTICS</p> <p>Sound power: max 55dba idle, 60dba operating Sound pressure: 55dba operating</p>
<p>Printer Specification</p> <p>RECEIPT PRINTER</p> <p>40 column graphics printer Capacity up to 5000 transactions 4.4" (112mm) receipts Form length 4.4-7.5" (112-190mm) Optional sideways feature allows 80 column x 20 row mini statement</p> <p>JOURNAL PRINTER</p> <p>40 column graphics thermal or dot matrix printer Capacity up to 5000 @ 5 line journal entries</p>		
<p>Technical Specification</p> <p>PLACEMENT</p> <p>Front, rear or vestibule access</p>		



Transforming Transactions into Relationships



The future of self-service software solutions

NCR Financial Solutions Group Ltd
 1700 South Patterson Boulevard, Dayton, Ohio, 45479

NCR continually improves products as new technologies and components become available. NCR, therefore, reserves the right to change specifications without prior notice.

All features, functions and operations described herein may not be marketed in all parts of the world. Consult your NCR representative for the latest information.

www.ncr.com

©2001 NCR Corporation

SP 6065