



# Personas™ 75

## Full-function interior

- **Easy to use, easy to see**
- **Expand your service offering**
- **New revenue opportunities**
- **Color customize to deliver brand recognition**

*NCR's intelligent and highly functional Self-Service TouchPoints™ can turn your existing infrastructure into a strategic weapon. Our solutions help you to build better customer relationships, generate new revenue streams and migrate more transactions to a cost-efficient channel. Our web enabled Self-Service TouchPoints are the physical presence required for e-commerce fulfilment and mobile lifestyles. Making the virtual tangible.*

The **Personas 75** offers key opportunities for expanding the self-service channel and making the most of what, for many people, is the main point of contact with their bank. It is a full-function interior ATM, providing a range of services such as dispensing cash, cashing checks, paying bills, account inquiries, passbook and document printing.

As well as offering banks a convenient method of performing activities traditionally handled by the teller, there is a clear opportunity for generating additional revenue by dispensing non-cash items such as stamps, tickets and coupons. The high quality graphic printers also allow for the easy inclusion of logos and other graphical images. The receipt printer can be used, for example, to print discount vouchers and the statement printer for loan agreements.

The design is the result of exhaustive research, development, and testing – so customers will find it convenient and easy to use with a large, highly visible color display. Importantly, since the **Personas 75** may be your customers' main point of contact, branding is also available. NCR offers a complete color customization service to match and reinforce your brand identity wherever the location.

The relatively compact size of the **Personas 75** means that it can be installed in a wide range of interior locations, with front or rear access and a vestibule variant ensuring that the customer can get cash – and more – in all environments.



To ensure your investment is protected, the modules in the **Personas 75** will be fully upgradeable and sidecar expandable.

The **Personas 75** is part of a comprehensive portfolio of Self-Service Solutions from NCR, focused on quality and reliability, on delivering an enhanced range of solutions for our customers, and an improved range of services for the consumer.

The **Personas 75** from NCR. Cash and more.

# Specifications

<p><b>Multimedia Interface</b></p> <p>15" (381mm) VGA color screen with privacy filter option</p> <p>8 tactile function display keys or touchscreen interface</p> <p>Ruggedized tactile 16 key keyboard</p> <p>Swipe, dip or motorized card reader</p> <p>Motorized card reader with smart card option</p> <p>EMV 3.1.1 compliant smart card reader</p> <p>Private audio or digitized audio system</p>	<p>Statement/passbook feature for dual function</p> <p>9 pin dot matrix, magnetic read write, last line and page detect</p> <p><b>ENVELOPE DEPOSITORY</b></p> <p>Envelope length: 8" (203mm) min, 10" (254mm) max</p> <p>Envelope width: 3.875" (98mm) min, 4.375" (111mm) max</p> <p>Thickness: 0.5" (12.7mm) max</p>	<p><b>ACCESSIBILITY</b></p> <p>Subject to compliance with NCR site preparation and installation guidelines, the NCR P75 complies with ADAAG 4.34.2, 4.34.3, and 4.34.4. NCR cannot certify or warrant compliance with ADAAG 4.34.5.</p> <p><b>ELECTROMAGNETIC COMPATIBILITY Emission</b></p> <p>FCC Category A (USA)</p> <p>FTZ VDE 871/875 (Germany) Class A</p> <p>EN 55022 (1987) Class A</p> <p>CISPR 22 Class A</p> <p><b>Immunity</b></p> <p>EN 50082-1 Part 1 (1992)</p> <p>Generic Immunity Standard</p> <p>Radiated Immunity – IEC 801-3</p> <p>Electrostatic Discharge – IEC 801-2</p> <p>Fast Transients – IEC 801-4</p> <p><b>EMC Directives</b></p> <p>89/336/EEC EMC Directive</p> <p>92/31/EEC Amending EMC Directive</p> <p>73/23/EEC Low Voltage Directive</p> <p><b>SAFETY HOUSE COMPATIBILITY</b></p> <p>UL 291</p> <p>CAN/CSA-C22.2 no. 950 EN60 950</p> <p><b>ENVIRONMENTAL</b></p> <p>Operating temperature: 50°F (10°C) to 104°F (40°C)</p> <p>Relative humidity: 20% to 80%</p> <p><b>ACOUSTICS</b></p> <p>Sound power: max 55dba idle, 65dba operating</p> <p>Sound pressure: 55dba operating</p>
<p><b>Printer Specification</b></p> <p><b>RECEIPT PRINTER</b></p> <p>40 column graphics thermal printer</p> <p>Capacity up to 5000 transactions 4.4" (112mm) receipts</p> <p>Form length 4.4-7.5" (112-190mm)</p> <p>Optional sideways feature allows 80 column x 20 row mini statement</p> <p><b>JOURNAL PRINTER</b></p> <p>40 column graphics thermal or dot matrix printer</p> <p>Capacity up to 5000 @ 5 line journal entries</p> <p><b>STATEMENT PRINTER</b></p> <p>80 column letter quality thermal printer</p> <p>Capacity up to 800 sheets 12" (305mm)</p> <p>Form length 4-12" (102-305mm)</p> <p>Document capture</p> <p>Full graphics option</p> <p><b>PASSBOOK PRINTERS</b></p> <p>Page-turning passbook printer for horizontally stitched books</p> <p>4" (102mm) bunching capability</p> <p>Document capture</p> <p>24 pin dot matrix, magnetic read write, last line and page detect</p>	<p><b>Technical Specification</b></p> <p><b>PRODUCT DIMENSIONS</b></p> <p>Height 55.87" (1419mm)</p> <p>Width 31.89" (810mm)</p> <p>Depth 36.97" (939mm)</p> <p>Weight 1553lb (704.3kg) – UL 291</p> <p><b>DISPENSERS</b></p> <p>1,2,3 or 4 denomination options with bunch, retract and purge capability</p> <p>NCR universal polycarbonate multimedia cassette with 11.6" (295mm) capacity</p> <p>Optional 4 denomination coin dispenser</p> <p><b>SECURITY</b></p> <p>Physical</p> <p>UL 291 Level 1</p> <p>High level – meets RAL 626/3</p> <p>UK – Special – (TL 30 Derivative)</p> <p>CEN Grade A3</p> <p><b>INFORMATION</b></p> <p>HI-BAPE (DES)</p> <p>EKC (DES, RSA limited to initial key exchange), enhanced physical protection</p> <p><b>ELECTRONIC PLATFORM</b></p> <p>Multiple Pentium® processing</p>	



Transforming Transactions into Relationships



The future of self-service software solutions

NCR Financial Solutions Group Ltd  
1700 South Patterson Boulevard, Dayton, Ohio, 45479

NCR continually improves products as new technologies and components become available. NCR, therefore, reserves the right to change specifications without prior notice.

All features, functions and operations described herein may not be marketed in all parts of the world. Consult your NCR representative for the latest information.

[www.ncr.com](http://www.ncr.com)

©2001 NCR Corporation

SP 6062